

Rigidur Nature Line floor adhesive



Material

- Industrial adhesive which contains no solvents or hazardous substances for the bonding of Rigidur Flooring Elements.

Area of use

- For the bonding of shiplap edges on all Rigidur Flooring Elements and the bonding of an additional layer of Rigidur H boards to pre-installed Rigidur Flooring Elements.

Substrate properties

- Ensure that the edge area of the Rigidur Flooring Elements is clean, smooth and free of dust before applying adhesive. Cuts must be made cleanly to ensure a maximum joint width of 2 mm between Flooring Elements. Any existing joints can be filled with Rigidur joint filler.

Processing

- Rigidur floor adhesive should be applied according to the Rigidur guidelines for floors. The guideline can be downloaded at www.rigidur.com
- Please also note the additional information on the Rigidur floor adhesive label.

Safety information

- As for all Rigips products, the safety datasheet for this product can be supplied to professional processors on request or found at www.rigips.com.

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.

Rigidur Nature Line floor adhesive

Technical data			
Designation	Rigidur Nature Line floor adhesive		
Container size	Bottle	1	[kg]
Processing	Material consumption	ca. 0.045	[kg/m ²]
	Processing time	ca. 10	[minutes]
	Processing temperature	7 bis 25	[°C]
	Coverage	ca. 22	[m ² /bottle]
Storage	Can be stored for 12 months unopened. Use up open bottles promptly. Store protected from frost.		

The values given in this product data sheet solely describe the performance characteristics of the products. Rigips-Systems also have far-reaching structural-physical and static properties, which can be found in our system documentation (e.g. Planen und Bauen).

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.