

Declaration of Performance

Glasroc® F MultiBoard



Rigips

SAINT-GOBAIN

1 Unique identification code of the product type:	Glasroc F MultiBoard
2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	Glasroc F MultiBoard: 6mm (EN 15283 - GM-F, GM-H1), 10mm, 12.5mm (EN 15283 - GM-F)
3 Intended use/s:	Plasterboard lining
4 Manufacturer:	British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0) 115 945 1000
5 Authorised representative:	N/A
6 System/s of AVCP:	System 4 generally System 3 Reaction to Fire
7 Harmonised standard:	EN 15283-1:2008 + A1:2009
Notified body/ies:	MPA Hannover (NB 0764)
Performed:	Reaction to Fire
Under:	System 3
8 European Assessment Document:	N/A
European Technical Assessment:	N/A
Technical Assessment Body:	N/A
Notified body/ies:	N/A
9 Declared performance/s:	The characteristics in the table below apply to all products mentioned in 2 above.

Essential characteristics	Performance	Harmonised technical specification
Longitudinal flexural strength (F)	258N (6mm) 430N (10mm) 538N (12.5mm)	EN 15283-1:2008 + A1:2009
Transverse flexural strength (F)	101N (6mm) 168N (10mm) 210N (12.5mm)	EN 15283-1:2008 + A1:2009
Shear strength (\downarrow)	NPD	EN 15283-1:2008 + A1:2009
Reaction to Fire (R2F)	A1	EN 15283-1:2008 + A1:2009
Water vapour permeability (μ)	10	EN 15283-1:2008 + A1:2009
Impact resistance ¹ (\rightarrow I)	See manufacturer's literature	EN 15283-1:2008 + A1:2009
Direct airborne sound insulation ¹ (R)	See manufacturer's literature	EN 15283-1:2008 + A1:2009
Acoustic absorption ¹ (α)	See manufacturer's literature	EN 15283-1:2008 + A1:2009
Thermal resistance (as conductivity) (λ)	0.3W/mK	EN 15283-1:2008 + A1:2009

¹ These characteristics are system dependent and will be provided in manufacturer's literature based upon intended use.

Declaration of Performance

Glasroc® F MultiBoard

CE




Rigips

SAINT-GOBAIN

10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



East Leake 26/03/2019

Matt Pullen, Managing Director, British Gypsum

Place and date of issue



Rigips

SAINT-GOBAIN

