

Glasroc<sup>®</sup> F MultiBoard

## CE Unique identification code of the product type OBAIN 1

- 2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
- Intended use/s: 3

10mm, 12.5mm (EN 15283 - GM-F)

Glasroc F MultiBoard

Glasroc F MultiBoard: 6mm (EN 15283 - GM-F, GM-H1),

3	Intended use/s:		Plasterboard lining	
4 5 6			British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0) 115 945 1000	
7	Harmonised standard: Notified body/ies: Performed: Under:		System 3 Reaction to Fire EN 15283-1:2008 + A1:2009 MPA Hannover (NB 0764) Reaction to Fire System 3	
8	European Assessment Document: European Technical Assessment: Technical Assessment Body: Notified body/ies:		N/A N/A N/A	
9	Declared performance/s:		The characteristics in the table below apply to all products mentioned in 2 above.	
	Essential characteristics	Performance		Harmonised technical specification
	Longitudinal flexural strength (F)	258N (6mm) 430N (10mm) 538N (12.5mm)		EN 15283-1:2008 + A1:2009
	Transverse flexural strength (F)	101N (6mm) 168N (10mm) 210N (12.5mm)		EN 15283-1:2008 + A1:2009
	Shear strength ( <b>l</b> †)	NPD		EN 15283-1:2008 + A1:2009
	Reaction to Fire (R2F)	Al		EN 15283-1:2008 + A1:2009
	Water vapour permeability ( $\mu$ )	10		EN 15283-1:2008 + A1:2009
	Impact resistance¹ (→I)	See manufacturer's lit	erature	EN 15283-1:2008 + A1:2009
	Direct airborne sound insulation <sup>1</sup> (R)	See manufacturer's literature		EN 15283-1:2008 + A1:2009
	Acoustic absorption <sup>1</sup> ( $\alpha$ )	See manufacturer's lit	erature	EN 15283-1:2008 + A1:2009
	Thermal resistance (as conductivity) ( $\lambda$ )	0.3W/mK		EN 15283-1:2008 + A1:2009

<sup>1</sup> These characteristics are system dependent and will be provided in manufacturer's literature based upon intended use.

## **Declaration of Performance**



Glasroc<sup>®</sup> F MultiBoard

## ce Rigips

## 10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

SAINT-GOBAIN

Signed for and on behalf of the manufacturer by:



East Leake 26/03/2019

Matt Pullen, Managing Director, British Gypsum Place and date of issue



