


Product data sheet

RigiProfil MultiTec UW 150





Product description: Metal stud according to DIN 18182-1 / DIN EN 14195 made of sheet steel according to DIN EN 10346. Material tolerances according to DIN EN 10143.

Area of application: For the construction of substructures in gypsum plasterboard systems.













Oberfläch MultiTec

Korrosionsschutz

Anwendung Innenraum

Baustoffklasse

Blechdick

Lagerung

Technical specifications

Usage

RigiProfil MultiTec is the efficient system profile from Rigips, which is used to create substructures in plasterboard systems. A special feature of RigiProfil is the special MultiTec surface structure, which offers a variety of advantages in sound insulation and processing. RigiProfil complies with the requirements of DIN 18182-1 and DIN EN 14195 and is manufactured from steel of the grade DX51D+Z (material no. 1.0226) by cold forming.

Parameters	Sign	Value	UOM	Drawing
Dimensions				
Metal thickness	t	0.6	mm	
Profile hight	h	150.2	mm	Δ h
	Nominal	150	mm	
Profile width	b	39.8	mm	
	Nominal	40	mm	
Length	I	4,000	mm	
Profile parameter	l _{yy}	389,872	mm ⁴	

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.





Product data sheet

RigiProfil MultiTec UW 150

Parameters	Sign	Value	Unit	Certification		
Material						
Type of material		Galvanised sheet steel		EN 10346		
Material		DX51D+Z				
Corrosion protection		Z100		EN 14195		
Surface		MultiTec structure				
Typesetting						
Туре		UW150x40x06-Z100		DIN 18182-1		
		U/40/150/40		EN 14195		
Building material class						
Fire behaviour		A1		EN 13501-1		
Miscellaneous						
Additional Note		RigiProfil MultiTec is European patented (No. EP 3 017 120)				
Notes						
Storage		Dry Flat and level Air access				
Shelf Life		Unlimited				
Form of delivery		According to Pricelist				
Waste key		17 04 05				

The values listed in this product data sheet only reflect the performance characteristics of the products. In addition, gypsum plaster systems have structural and structural properties, which can be found in our system documentation (e. g. Planen und Bauen).

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.

