


Product data sheet

Rigips reinforcing stud UA 75-2



Product description: Metal stud according to DIN 18182-1 / DIN EN 14195 made of sheet steel according to DIN EN 10346. Material tolerances according to DIN EN 10143.

Area of application: For the construction of substructures in gypsum plasterboard systems e.g. in reinforced door openings.



Oberfläche
glatt




Korrosions-
schutz



Anwendung
Innenraum



Baustoffklasse




Blechdicke



Lagerung

Technical specifications

Parameters	Sign	Value	UOM	Drawing
Dimensions				
Metal thickness	t	2	mm	
Profile height	h	73.8	mm	
	Nominal	75	mm	
Profile width	b	39.0	mm	
	Nominal	40	mm	
Length	l	2,600 / 2,750 / 3,000 / 3,250 / 3,500 / 3,750 / 4,000 / 4,250 / 4,500 / 5,000 / 5,500 / 6,000	mm	
Profile parameter	I_{yy}	255,177	mm ⁴	

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.

Product data sheet

Rigips reinforcing stud UA 75-2

Parameters	Sign	Value	Unit	Certification
Material				
Type of material		Galvanised sheet steel		EN 10346
Material		DX51D+Z		
Corrosion protection		Z100		EN 14195
Surface		Smooth		
Building material class				
Fire behaviour		A1		EN 13501-1
Miscellaneous				
Additional Note		Oblong perforation 8.2 x 40 mm, double row, center distance 34 mm		
Notes				
Storage		Dry Flat and level Air access		
Shelf Life		Unlimited		
Form of delivery		According to Pricelist		
Waste key		17 04 05		

The values listed in this product data sheet only reflect the performance characteristics of the products. In addition, gypsum plaster systems have structural and structural properties, which can be found in our system documentation (e. g. Planen und Bauen).

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.