

DECLARATION OF PERFORMANCE

No.: Rigips_1_Mann_Aktionsverbundplatte_30_LE_2207

- (1) *Unique identification code of the product-type*
Rigips 1-Mann Aktionsverbundplatte 30
- (2) *Intended use/es*
**Gypsum based board from reprocessing: Floor element for interior application
A 9,5 EPS 20, Typ P (EN 13950)**
- (3) *Manufacturer*
**Saint-Gobain Rigips GmbH
Schanzenstr. 84
D-40549 Düsseldorf**
- (4) *Authorised representative*
N/A
- (5) *System/s of AVCP*
**System 3 for reaction to fire
System 4 for all other properties**
- (6a) *Harmonised standard*
EN 13950:2014
- Notified body/ies*
Materialprüfanstalt für das Bauwesen und Produktionstechnik (MPA H) (0764)
- (6b) *European Assessment Document*
N/A
- European Technical Assessment*
N/A
- Technical Assessment Body*
N/A
- Notified body/ies*
N/A



(7) Declared performance/s

Essential characteristics	Performance
Reaction to fire (R2F)	E
Flexural strength	NPD
Water vapour permeability (to control water vapour diffusion) specified as water vapour diffusion resistance	0.538 (m ² ·K)/W
Thermal resistance	0.538 (m ² ·K)/W
Dangerous substances (DS)	NPD
Impact resistance Airborne sound insulation (R) Acoustic absorption (α)	See system documentation of Saint-Gobain Rigips GmbH or from the local supplier


(8) Appropriate Technical Documentation and/or Specific Technical Documentation
N/A


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 15. July 2022




Raimund Heini, Managing Director


Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany



CE	
 Saint-Gobain Rigips GmbH Schanzenstr. 84 D-40549 Düsseldorf	
13	
Rigips_1_Mann_Aktionsverbundplatte_30_LE_2207	
EN 13950:2014	
Gypsum based board from reprocessing: Floor element for interior application A 9,5 EPS 20, Typ P (EN 13950)	
Notified body/ies: 0764	
Reaction to fire (R2F)	E
Flexural strength	NPD
Water vapour permeability (to control water vapour diffusion) specified as water vapour diffusion resistance	0.538 (m ² ·K)/W
Thermal resistance	0.538 (m ² ·K)/W
Dangerous substances (DS)	NPD
Impact resistance Airborne sound insulation (R) Acoustic absorption (α)	See system documentation of Saint-Gobain Rigips GmbH or from the local supplier

