

DECLARATION OF PERFORMANCE

No.: Rigips_Abschlussprofil_14_25_05_verzinkt_LE_2202

(1) *Unique identification code of the product-type*
Rigips Abschlussprofil 14 / 25-05 verzinkt

(2) *Intended use/es*
**Metal bead for internal plastering
Stop bead (EN 14353)**

(3) *Manufacturer*
**Saint-Gobain Rigips GmbH
Schanzenstr. 84
D-40549 Düsseldorf**

(4) *Authorised representative*
N/A

(5) *System/s of AVCP*
System 4

(6a) *Harmonised standard*
EN 14353:2007+A1:2010

Notified body/ies
Internal

(6b) *European Assessment Document*
N/A

European Technical Assessment
N/A

Technical Assessment Body
N/A

Notified body/ies
N/A

(7) Declared performance/s


Essential characteristics	Performance
Reaction to fire (R2F) (in unprotected condition)	A1
Bending behaviour	Requirements met
Dangerous substances (DS)	NPD

(8) Appropriate Technical Documentation and/or Specific Technical Documentation
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 04. February 2022



Raimund Heini, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany

CE	
Saint-Gobain Rigips GmbH Schanzenstr. 84 D-40549 Düsseldorf	
13	
Rigips_Abschlussprofil_14_25_05_verzinkt_LE_2202 EN 14353:2007+A1:2010	
Metal bead for internal plastering Stop bead (EN 14353)	
Notified body/ies: N/A	
Reaction to fire (R2F) (in unprotected condition)	A1
Bending behaviour	Requirements met
Dangerous substances (DS)	NPD

