

## **DECLARATION OF PERFORMANCE**

No.: Rigitone\_Mix\_LE\_2207

- (1) *Unique identification code of the product-type*  
**Rigitone Mix**
- (2) *Intended use/es*  
**Jointing material for plasterboards  
4A (EN 13963)**
- (3) *Manufacturer*  
**Saint-Gobain Rigips GmbH  
Schanzenstr. 84  
D-40549 Düsseldorf**
- (4) *Authorised representative*  
**N/A**
- (5) *System/s of AVCP*  
**System 3 for reaction to fire  
System 4 for all other properties**
- (6a) *Harmonised standard*  
**EN 13963:2005/AC:2006**
- Notified body/ies*  
**Materialprüfanstalt für das Bauwesen und Produktionstechnik (MPA H) (0764)**
- (6b) *European Assessment Document*  
**N/A**
- European Technical Assessment*  
**N/A**
- Technical Assessment Body*  
**N/A**
- Notified body/ies*  
**N/A**



(7) Declared performance/s


Essential characteristics	Performance
Reaction to fire (R2F) (for unprotected installation situations)	E
Flexural strength	NPD

(8) Appropriate Technical Documentation and/or Specific Technical Documentation  
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Düsseldorf, 12. August 2021



Raimund Heini, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany



<b>CE</b>	
<b>Saint-Gobain Rigips GmbH</b> Schanzenstr. 84 D-40549 Düsseldorf	
<b>15</b>	
<b>Rigitone_Mix_LE_2207</b> <b>EN 13963:2005/AC:2006</b>	
<b>Jointing material for plasterboards</b> <b>4A (EN 13963)</b>	
Notified body/ies: 0764	
Reaction to fire (R2F) (for unprotected installation situations)	E
Flexural strength	NPD

