

**DECLARATION OF PERFORMANCE**

No.: Vario\_30\_Fugenspachtel\_LE\_2208

(1) *Unique identification code of the product-type*  
**Vario 30 Fugenspachtel**

(2) *Intended use/es*  
**Jointing material for plasterboards  
4B (EN 13963)**

(3) *Manufacturer*  
**Saint-Gobain Rigips GmbH  
Schanzenstr. 84  
D-40549 Düsseldorf**

(4) *Authorised representative*  
**N/A**

(5) *System/s of AVCP*  
**System 3 for reaction to fire  
System 4 for all other properties**

(6a) *Harmonised standard*  
**EN 13963:2005/AC:2006**

*Notified body/ies*  
**Materialprüfanstalt für das Bauwesen und Produktionstechnik (MPA H) (0764)**

(6b) *European Assessment Document*  
**N/A**

*European Technical Assessment*  
**N/A**

*Technical Assessment Body*  
**N/A**

*Notified body/ies*  
**N/A**



(7) Declared performance/s


Essential characteristics	Performance
Reaction to fire (R2F) (for unprotected installation situations)	A1
Flexural strength	NPD

(8) Appropriate Technical Documentation and/or Specific Technical Documentation  
N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 15. August 2022



Raimund Heini, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany



<b>CE</b>	
<b>Saint-Gobain Rigips GmbH</b> Schanzenstr. 84 D-40549 Düsseldorf	
<b>13</b>	
<b>Vario_30_Fugenspachtel_LE_2208</b> <b>EN 13963:2005/AC:2006</b>	
<b>Jointing material for plasterboards</b> <b>4B (EN 13963)</b>	
Notified body/ies: 0764	
Reaction to fire (R2F) (for unprotected installation situations)	A1
Flexural strength	NPD

